

DATASHEET

Chicago Metallic™ Monolithic




Sounds Beautiful

Chicago Metallic™ Monolithic

- T and Omega shaped grid for the installation of Rockfon® Mono Acoustic and a variety of boards
- Quick and easy click system reduces time and installation costs
- Single layer system for reduced plenum heights
- Simple grid without the need for accessories

Cross-section



Compatible tiles

Concealed








Coupling

Joggled end





Assortment

Product group		Component description	Height (mm)	Length (mm)	Colour	Pcs per pack	Lm per pack	Kg per pack	Carton per pallet	Kg per pallet
Main runner										
MONO T35 MR		Monolithic main runner T35	38	3600	69	20	72	37.1	32	1187
Cross tee										
MONO HAT35 CT		Monolithic cross furring channel	22.23	1200	69	50	60	25	48	1200
Wall angle options										
MONO C40		Galvanised C Channel trim 30 x 40.5 x 30 x 3050mm	40.5	3050	69	10	30.5	10.74	60	666.4
Accessories										
NH CLIP		Intersection clip for nonius				200		1.3		
NH 90		Upper part nonius hanger	85			100		2.4		

Contact Rockfon® for the full range of wall angles and accessories.



Position of slots and suspension holes

Product group	Component description	Height (mm)	Length (mm)	Slots	Distance between slots (mm)
MONO T35 MR	Monolithic main runner T35	38	3600	18	 100 / 200 / 16 x 200 / 100
MONO HAT35 CT	Monolithic cross furring channel	22.23	1200	0	 1200

Performance



Load bearing capacity

Kg/m ²		
Hanger distance (mm)	Module size (mm)	Maximum deflection
		3.3 mm
1200	1200 x 400	13.9
1200	1200 x 600	12



Reaction to fire

A1



Corrosion Resistance

B



Environment

Fully recyclable



Understanding the performance of Chicago Metallic™ grids and accessories



Reaction to fire

Reaction to fire is classified in accordance with EN 13501-1. Chicago Metallic steel grids and accessories are non-combustible.



Fire resistance

A range of Chicago Metallic steel grids are tested in combination with different Rockfon tiles and are classified in accordance with European norm EN 13501-2 and/or national norms.



Corrosion resistance

Chicago Metallic products produced from hot dip galvanised steel following the Sendzimir process comply with the corrosion classes of the product standard EN 13964 (A, B, C, D). The standard systems in class B are protected with 100 g/m² zinc evenly applied on both sides. The enhanced corrosion resistance (ECR) systems and accessories in class C or D have respectively a layer of 100 g/m² and 275 g/m² zinc evenly applied on both sides and are protected with an additional layer of 20 micron paint per side.



Load bearing performance

The load bearing performance (max. kg/m² load applicable to the grid system without exceeding the allowable deflection of the individual components) is tested in accordance with the EN 13964 standard. The accumulative value of the system deflection, shown on the data sheets, does not exceed the max. deflection as given in class 1 of the standard. Special project configurations deviating from the standard module sizes mentioned in the data sheets must be calculated by Rockfon technical services.

06.2024 | All colour codes mentioned are based on the NCS - Natural Colour System® property of and used on license from NCS Colour AB, Stockholm 2012 or the RAL colour standard. Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

Sounds Beautiful

